


DISCOVERY

Energy Services

COMPLETIONS AND WORKOVER RIG RIG DISCOVERY 4 SPECIFICATIONS BROCHURE



ISO 9001: 2008
ISO 14001: 2004
OHSAS 18001: 2007
BUREAU VERITAS
Certification



N° C0223270 / N° C0223271 / N° C0223272

HIGHLIGHTS

Name:	Discovery 4
Brand	Taylor
Power:	500 HP
Year:	2004
Double Drum:	Drawworks and Sandline Drums
Type:	Self-propelled Land Rig
Static Hook Load:	205.000 Libras
Service:	12.000 FT TUBING 3-1/2"



Rig Discovery-4 In operations



CARRIER


Specifications	Data
Manufacturer	Taylor
Model	Taylor 4 axle, 8x4 Drive
Brakes	Air brakes in all wheels
Steering	Hydraulic powered
Front axles	2
Rear axles	2
Headlights	Stop and taillights
Reflectors	Air horn
Cab	One man, washer and wiper
Mirrors	Two rear view mirrors



MAST AND SUBSTRUCTURE

MAST

Specifications	Data
Manufacturer	PENCO
Model	96/205
Type	Telescoping double
Clear Height	96 ft
Static Hook Load	205.000 Lbs
Drilling line size	1"



MAST SUBSTRUCTURE

Specifications	Data
Manufacturer	Prodimetales
Year	2010
Type	Telescoping (Low boy)
Height	10 - 14ft
Capacity	250.000 Lbs
Weight	12.000 Kg
Rotary Table:	Sentry 17-1/2" and 250 Ton

HOISTING EQUIPMENT

DRAWWORKS

Specifications	Data
Manufacturer	Taylor
Year	2004
Model	DD42-148 (Band)
Size	18.75" x 34"
Single line pull	38.000 Lbs
Shaft Diameter	6-1/2"
Horse power rating	500 HP
Drum Capacity	16.000 Ft of 9/16"



AUXILIARY BRAKE

Specifications	Data
Manufacturer	Taylor
Reference	42x 12 blocks

HOISTING EQUIPMENT

SANDLINE DRUM

Specifications	Data
Manufacturer	Taylor
Model	
Size	12.75"
Drum Capacity	16.000 ft of 9/16«Wire Rope

TRANSMISSION

Specifications	Data
Manufacturer	Allison
Model	Allison CLT 754
Type	Automatic
Power shift	From cab and rear control

ENGINE

Specifications	Data
Manufacturer	Caterpillar
Model	C-15/
Rating	520 HP @ 2100 rpm
Exhaust	With spark arrestor
Air compressor	Driven from engine
Emergency stop	Standard





HOISTING EQUIPMENT

HYDRAULIC SYSTEM

Specifications	Data
Hydraulic pump	C.MODEL 37X-50 GPM
Oil Tank	190 Gal
Max. Pressure	2000 PSI @ 2100 rpm
System rating pressure	3000 PSI
Raising Cylinder	Three stages (hydraulic)
Jackscrews	4 hydraulic leveling jacks

HANDLING WINCH

Specifications	Data
Type	Hydraulic powered
Capacity	7.000 Lbs
Rated line pull	100 fpm and 2.000 PSI
Line	325 ft of 1/2"
Fail-safe brake	Included

TRAVELING BLOCK

Specifications	Data
Manufacturer	IDEAL
Type	Hook block
Reference	100
Load capacity	100 TON
Sheaves	3 sheaves 24in for 1in line
Link elevators	100 TON, 6 ft

ROTARY SYSTEM

ROTARY TABLE

Specifications	Data
Manufacturer	Sentry
Load capacity	250 Ton
Reference	SI-RT-175 X 44
Load capacity	150 TON
Size	17-1/2"
Max. Working torque	10.132 ft.Lbs
Max speed	300 rpm



KELLY SYSTEM

Specifications	Data
Kelly type	Square 3-1/2" X 40ft
Bottom conexión	3-1/2 IF pin
Top conexión	6-5/8 Reg LH box
Kelly drive bushing	Square drive 17-1/2"
Kelly master Bushing	Included
Load capacity	150 TON
Size	17-1/2"
Max. Working torque	10.132 ft.Lbs
Max speed	300 rpm

CIRCULATING SYSTEM

MUD PUMP

Specifications	Data
Manufacturer	DOWELL SCHLUMBERGER
Reference	PD-08 TRIPLEX PUMP
Liners	4-1/2"
Stroke lenght	5"
Engine	Detroit 12V-71
Horse power rating	350 HP
Year	2005
Transmission	Mechanic fuller RTO-2008



CIRCULATING SYSTEM

MUD TANKS

Specifications	Data
Qty	2
Capacity	250 BBL (TOTAL: 500 BBL)
Agitators	3
Cetrifuge	4X4 (Electric engine of 40HP)
Type	Fast move (Low boy)
Fixed poor boy	Included
Electric instalation	Explosion proof (6 lamps)
Mud mixing Hopper	Included



WELL CONTROL SYSTEM*

ANULAR BOP

Specifications	Data
Manufacturer	Hydril
Size	7-1/16 X 5M
Top conexión	Studded
Bottom conexión	Flanged
Max. Working pressure	5000 PSI



RAM BOP

Specifications	Data
Manufacturer	Hydril
Size	7-1/16 X 5M
Top conexión	Studded
Bottom conexión	Flanged
Max. Working pressure	5000 PSI
Rams	Blind Rams and Pipe rams
Pipe rams	3-1/2 and 2-7/8



CHOKE MANIFOLD

Specifications	Data
Reference	2-1/16 X 5M
Valves	9 gate flanged valve 2-1/16 X 5M
Conexiones	2" Fig. 1502
Chokes	2 graduable chokes

*all well control equipment is as per API RP 53

WELL CONTROL SYSTEM*

ACCUMULATOR UNIT

Specifications	Data
Bottles	7 of 10 Gal
Working pressure	3000 PSI
Pre-charge pressure	1000 PSI
Hydraulic pump	Triplex
Pneumatic pump	Included
Four way rotary valve	4
Pressure regulator	3
Electric system	Explosion proof





WELL CONTROL SYSTEM*

POOR BOY

Specifications	Data
Size	24"
Type	Fixed at mud tank
Liquid outlet	8"
Gas outlet	3"





POWER SYSTEM

GENERATORS

Specifications	Data
Manufacturer	General power
Qty	2
Capacity	131 KVA
Cabin	Isolated cabin
Model	GP131S
Conexions	Explosion proof (Appleton)



MANUAL TOOLS

Specifications	Data
Pipe wrenches	2 of each size (24, 36, 48 y 60)
Chain wrenches	24 and 36"


HYDRAULIC TONG

Specifications	Data
Manufacturer	Foster
Tubing sizes	2-3/8, 2-7/8, 3-1/2
Reference	58-93R
Type	Hydraulic powered



MANUAL TONGS

Specifications	Data
Manufacturer	BJ
Type	C
Range	3-1/2 to 5-1/2" and 7 to 8-1/2"
Torque rating	Up to 35.000 Lbs




ELEVATORS

Specifications	Data
Tubing elevators	90° for 2-3/8, 2-7/8 and 3-1/2
Drill pipe elevator	18° for 3-1/2
Torque rating	Up to 35.000 Lbs
Type	Latch



SLIPS

Specifications	Data
Pneumatic slips	Cavins for 100 tons (2-3/8 to 3-1/2)
Rotary slips	Varco - BJ (2-7/8 to 3-1/2) 150 tons
Drill Collar slips	4-3/4 Drill Collar slips
Safety clamp	4-3/4 Drill Collars



MINI CAMP

Specifications	Data
Units	3
Beds	2 or 4 for every room
Bathroom	1 for each room
Year	2010
Skidd	Yes
Refrigerator	For Coman
Dining room	included





INSTRUMENTATION

WEIGHT INDICATOR

Specifications	Data
Manufacturer	Martin Decker
Type	Clipper
Lines	6 lines of 1« Wire
Range	0-280.000 Lbs

JOINT TORQUE

Specifications	Data
Manufacturer	Martin Decker
Range	0-10.000 ft.Lbs
Type	Pressure Cell

ROTARY TORQUE

Specifications	Data
Manufacturer	Forum
Range	0-500

STROKE COUNTER

Specifications	Data
Model	5700
Totalizer	Included
Mud pumps	2

MISCELLANEOUS

SWABBING EQUIPMENT

Specifications	Data
Oil saver	Guiberson HD
Swivel rope socket	Guiberson for 9/16
Sinker bars	2 of 10ft
Swab mandrel	Knuckle joint type (2)
Hydraulic pump	Including a hose of 50ft
Dephtometer	Cavins
Lubricator	4"
Swabbing tree	4" with 3 gate valves (4"X5M)

SAFETY EQUIPMENT

Specifications	Data
Fall Protection	Full body harnesses, Body belts, Lanyards , SRL'S.
Low speed descender	Included
Climbing assist system	Included
Gas detector	Portable
Breathalyzer	Portable

